

Safety data sheet

ELASTOPOR*P 15970R RESIN

Revision date : 2006/04/20
Version: 3.0

Page: 1/6
(30237755/MDS_GEN_US/EN)

1. Substance/preparation and company identification

Company
BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932

24 Hour Emergency Response Information
CHEMTREC: (800) 424-9300
BASF HOTLINE: (800) 832-HELP

Chemical family: resin
Synonyms: Urethane System Resin Component

2. Composition/information on ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
56-81-5	< 45.0 %	Polyol
	< 10.0 %	glycerol
	< 40.0 %	Flame Retardant
460-73-1	< 5.0 %	1,1,1,3,3-pentafluoropropane
	< 1.0 %	Catalyst
	< 2.0 %	Surfactant

3. Hazard identification

Emergency overview

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
CONTAINS MATERIAL WHICH CAN CAUSE NERVOUS SYSTEM DAMAGE.

Potential health effects

Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Ingestion may cause gastrointestinal disturbances.

Information on: Fluorocarbons

At levels above the recommended exposure limit, the fluorocarbon acts as a weak narcotic. Acute overexposure causes tremors, confusion, irritation, suffocation, and may result in cardiac sensitization.

Information on: Glycerin

Ingestion of large amounts of glycerine may result in nausea, vomiting, gastric irritation, and kidney disorders. Glycerine can exert systemic effects when given orally in very large doses.

Irritation:

Irritating to respiratory system.

Information on: Polyol

Contact with the eyes and skin may result in irritation.

Repeated dose toxicity:

Safety data sheet

ELASTOPOR*P 15970R RESIN

Revision date : 2006/04/20
Version: 3.0

Page: 2/6
(30237755/MDS_GEN_US/EN)

No other known chronic effects.

Medical conditions aggravated by overexposure:

Data available do not indicate that there are medical conditions that are generally recognized as being aggravated by exposure to this substance/product.

4. First-aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Wash affected areas thoroughly with soap and water. Immediate medical attention required.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Immediate medical attention required.

5. Fire-fighting measures

Flash point: approx. > 93 °C (open cup)
Autoignition: No data available.

Suitable extinguishing media:

water, dry extinguishing media, carbon dioxide, foam

Hazards during fire-fighting:

No particular hazards known.

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

6. Accidental release measures

Cleanup:

Spills should be contained, solidified, and placed in suitable containers for disposal.

Safety data sheet

ELASTOPOR*P 15970R RESIN

Revision date : 2006/04/20
Version: 3.0

Page: 3/6
(30237755/MDS_GEN_US/EN)

7. Handling and storage

Handling

General advice:

Product should not be mixed with air above atmospheric pressure for leak testing or any other purpose. Use dry nitrogen to transfer or leak test equipment pressurized with product.

Protection against fire and explosion:

No explosion proofing necessary.

Storage

General advice:

Product that is frozen and/or tending to sedimentation can be liquified or homogenized by careful application of indirect heat (do not use flames or direct contact with a heat source). Protect from direct sunlight. Keep in a cool, well-ventilated place. Avoid extreme heat. Store protected against freezing. Stored and transported in a cylinder under pressure. Must not be repacked by the customer.

Storage stability:

Storage temperature: 60 - 80 °F

Protect against moisture. Store in unopened original containers in a cool and dry place.

8. Exposure controls and personal protection

Components with workplace control parameters

glycerol	OSHA	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ;
	ACGIH	TWA value 10 mg/m3 Mist ;

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

General safety and hygiene measures:

Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. Wash soiled clothing immediately.

9. Physical and chemical properties

Form:	liquid
Odour:	faint odour, amine-like
Colour:	amber
pH value:	>= 7

Safety data sheet

ELASTOPOR*P 15970R RESIN

Revision date : 2006/04/20
Version: 3.0

Page: 4/6
(30237755/MDS_GEN_US/EN)

Boiling point:	15.6 °C	(103.43 mmHg)
Bulk density:	9.060 lb/USg	
Viscosity, dynamic:	900 mPa.s	(23 °C)
Miscibility with water:		slightly soluble

10. Stability and reactivity

Conditions to avoid:

> 80 degrees Fahrenheit

Avoid moisture. Avoid direct sunlight. Avoid excessive temperatures.

Hazardous reactions:

The product is chemically stable.

Decomposition products:

Hazardous decomposition products: carbon monoxide, carbon dioxide

Thermal decomposition:

No data available.

Corrosion to metals:

No corrosive effect on metal.

11. Toxicological information

12. Ecological information

13. Disposal considerations

Waste disposal of substance:

Incinerate in a licensed facility.

Dispose of in a licensed facility.

Do not discharge substance/product into sewer system.

Container disposal:

Return to the manufacturer with residual pressure. If cylinder is damaged, please contact supplier. Empty cylinders (all sizes) must be depressurized before they are returned to supplier. Depressurization will not relieve all pressure. Always seal cylinder valves for return.

14. Transport information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Safety data sheet

ELASTOPOR*P 15970R RESIN

Revision date : 2006/04/20
Version: 3.0

Page: 5/6
(30237755/MDS_GEN_US/EN)

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations

Registration status:
TSCA, US released / listed

State regulations

State RTK

<u>CAS Number</u>	<u>Chemical name</u>	<u>State RTK</u>
56-81-5	glycerol	MA, PA

CA Prop. 65:
THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

16. Other information

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 1

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

Local contact information

William Robert
1-734-324-5244

ELASTOPOR is a registered trademark of BASF Corporation or BASF AG

Safety data sheet

ELASTOPOR*P 15970R RESIN

Revision date : 2006/04/20

Version: 3.0

Page: 6/6

(30237755/MDS_GEN_US/EN)

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

BASF CORPORATION WILL NOT MAKE ITS PRODUCTS AVAILABLE TO CUSTOMERS FOR USE IN THE MANUFACTURE OF MEDICAL DEVICES WHICH ARE INTENDED FOR PERMANENT IMPLANTATION IN THE HUMAN BODY OR IN PERMANENT CONTACT WITH INTERNAL BODILY TISSUES OR FLUIDS.

END OF DATA SHEET