

SAFETY DATA SHEET



1. Identification

Product number 100507
Product identifier **100507 OEM E-Coat - LIGHT GREEN aerosol 340 g / 12 oz**
Company information Kardol Quality Products
9933 Alliance Rd
Cincinnati, OH 45242
Company phone 1-712-737-4993
Emergency telephone US CHEMTREC : (800) 424-9300
Emergency telephone outside US Not applicable.
Version # 01
Recommended use COATING
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Health hazards Serious eye damage/eye irritation Category 2A
Reproductive toxicity (the unborn child) Category 2
Specific target organ toxicity, single exposure Category 3 narcotic effects
Specific target organ toxicity, repeated exposure Category 2
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.
Precautionary statement
Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.
Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC) None known.
Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	20 - 40
Ethyl acetate		141-78-6	10 - 20
Propane		74-98-6	10 - 20
Isobutane		75-28-5	2.5 - 10
Isopropyl Alcohol		67-63-0	2.5 - 10
Methyl Ethyl Ketone		78-93-3	2.5 - 10
Methyl Isobutyl Ketone		108-10-1	2.5 - 10
n-Butyl Acetate		123-86-4	2.5 - 10
Propylene Glycol Monomethyl Ether Acetate		108-65-6	2.5 - 10
Toluene		108-88-3	2.5 - 10
Nitrocellulose		9004-70-0	1 - 2.5
Titanium dioxide		13463-67-7	1 - 2.5
Xylene		1330-20-7	1 - 2.5
Other components below reportable levels			2.5 - 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Powder. Alcohol resistant foam. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm	
Ethyl acetate (CAS 141-78-6)	PEL	1400 mg/m3	
Isopropyl Alcohol (CAS 67-63-0)	PEL	400 ppm 980 mg/m3	
Methyl Ethyl Ketone (CAS 78-93-3)	PEL	400 ppm 590 mg/m3	
Methyl Isobutyl Ketone (CAS 108-10-1)	PEL	200 ppm 410 mg/m3	
n-Butyl Acetate (CAS 123-86-4)	PEL	100 ppm 710 mg/m3	
Propane (CAS 74-98-6)	PEL	150 ppm 1800 mg/m3	
Titanium dioxide (CAS 13463-67-7)	PEL	1000 ppm 15 mg/m3	Total dust.
Xylene (CAS 1330-20-7)	PEL	435 mg/m3 100 ppm	

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Ethyl acetate (CAS 141-78-6)	TWA	400 ppm
Isobutane (CAS 75-28-5)	STEL	1000 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
Methyl Ethyl Ketone (CAS 78-93-3)	STEL	300 ppm
	TWA	200 ppm
Methyl Isobutyl Ketone (CAS 108-10-1)	STEL	75 ppm
	TWA	20 ppm
n-Butyl Acetate (CAS 123-86-4)	STEL	200 ppm
	TWA	150 ppm
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m ³
Toluene (CAS 108-88-3)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m ³
		250 ppm
Ethyl acetate (CAS 141-78-6)	TWA	1400 mg/m ³
		400 ppm
Isobutane (CAS 75-28-5)	TWA	1900 mg/m ³
		800 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	1225 mg/m ³
	TWA	500 ppm
Methyl Ethyl Ketone (CAS 78-93-3)		980 mg/m ³
	STEL	400 ppm
Methyl Isobutyl Ketone (CAS 108-10-1)		885 mg/m ³
	TWA	300 ppm
n-Butyl Acetate (CAS 123-86-4)	STEL	590 mg/m ³
	TWA	200 ppm
Propane (CAS 74-98-6)	STEL	300 mg/m ³
	TWA	75 ppm
		205 mg/m ³
		50 ppm
	STEL	950 mg/m ³
	TWA	200 ppm
		710 mg/m ³
		150 ppm
	TWA	1800 mg/m ³

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	1000 ppm
		560 mg/m3
	TWA	150 ppm
		375 mg/m3
		100 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Propylene Glycol Monomethyl Ether Acetate (CAS 108-65-6)	TWA	50 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
Methyl Ethyl Ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*
Methyl Isobutyl Ketone (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Propylene Glycol Monomethyl Ether Acetate (CAS 108-65-6) Can be absorbed through the skin.

Toluene (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3) Skin designation applies.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Skin protection

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state Gas.

Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	-156.0 °F (-104.4 °C) PROPELLANT estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	2.6 % estimated
Flammability limit - upper (%)	9.2 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Specific Gravity	0.744 estimated
VOC Content	Non-Flat Paint Products category; PWR (MIR) < 1.40; VOC COMPLIANT

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Nitrates. Halogens. Ammonia. Amines. Isocyanates. Fluorine. Caustics. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation.

Information on toxicological effects

Acute toxicity	Narcotic effects.	
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
<i>Dermal</i>		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l
<i>Oral</i>		
LD50	Rat	5800 mg/kg 2.2 ml/kg
Ethyl acetate (CAS 141-78-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 20000 mg/kg, 24 Hours
<i>Oral</i>		
LD50	Rabbit	4934 mg/kg
	Rat	11.3 ml/kg
Isobutane (CAS 75-28-5)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l
Isopropyl Alcohol (CAS 67-63-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	16.4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 10000 ppm, 6 Hours
<i>Oral</i>		
LD50	Rat	5.84 g/kg
Methyl Ethyl Ketone (CAS 78-93-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 10 ml/kg, 24 Hours
<i>Oral</i>		
LD50	Rat	2054 mg/kg
Methyl Isobutyl Ketone (CAS 108-10-1)		
Acute		
<i>Inhalation</i>		
LC50	Rat	2000 - 4000 ppm, 4 Hours
<i>Oral</i>		
LD50	Rat	2.08 g/kg

Components	Species	Test Results
n-Butyl Acetate (CAS 123-86-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 16 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	1087 ppm, 4 Hours 0.74 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	14130 mg/kg 12.2 ml/kg
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h
Propylene Glycol Monomethyl Ether Acetate (CAS 108-65-6)		
Acute		
<i>Dermal</i>		
LD50	Rat	> 2000 mg/kg, 24 Hours
<i>Oral</i>		
LD50	Rat	> 14.1 ml 5155 mg/kg
Titanium dioxide (CAS 13463-67-7)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 2.28 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	> 11000 mg/kg
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Mouse	6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours 12.5 - 28.8 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	5000 mg/kg
Xylene (CAS 1330-20-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 ml/kg, 4 Hours 12126 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	5922 ppm, 4 Hours

Components	Species	Test Results
Oral LD50	Mouse	5251 mg/kg
	Rat	3523 mg/kg
		10 ml/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Methyl Isobutyl Ketone (CAS 108-10-1)	2B Possibly carcinogenic to humans.
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	Prolonged exposure may cause chronic effects. May cause damage to organs through prolonged or repeated exposure.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours
Ethyl acetate (CAS 141-78-6)		
Aquatic		
Crustacea	EC50	Daphnia 560 mg/L, 48 Hours
Fish	LC50	Indian catfish (Heteropneustes fossilis) 200.32 - 225.42 mg/l, 96 hours
Isopropyl Alcohol (CAS 67-63-0)		
Aquatic		
Algae	IC50	Algae 1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia 13299 mg/L, 48 Hours
Fish	LC50	Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours
Methyl Ethyl Ketone (CAS 78-93-3)		
Aquatic		
Crustacea	EC50	Daphnia 520.0001 mg/L, 48 Hours

Components		Species	Test Results
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	> 400 mg/l, 96 hours
Methyl Isobutyl Ketone (CAS 108-10-1)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	492 - 593 mg/l, 96 hours
n-Butyl Acetate (CAS 123-86-4)			
Aquatic			
Algae	IC50	Algae	674.7 mg/L, 72 Hours
Fish	LC50	Fathead minnow (Pimephales promelas)	17 - 19 mg/l, 96 hours
Propylene Glycol Monomethyl Ether Acetate (CAS 108-65-6)			
Aquatic			
Crustacea	EC50	Daphnia	500.0001 mg/L, 48 Hours
Titanium dioxide (CAS 13463-67-7)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours
Toluene (CAS 108-88-3)			
Aquatic			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
Xylene (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Acetone	-0.24
Ethyl acetate	0.73
Isobutane	2.76
Isopropyl Alcohol	0.05
Methyl Ethyl Ketone	0.29
Methyl Isobutyl Ketone	1.31
n-Butyl Acetate	1.78
Propane	2.36
Toluene	2.73
Xylene	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1)	U002
Ethyl acetate (CAS 141-78-6)	U112
Methyl Ethyl Ketone (CAS 78-93-3)	U159
Methyl Isobutyl Ketone (CAS 108-10-1)	U161
Toluene (CAS 108-88-3)	U220
Xylene (CAS 1330-20-7)	U239

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.	

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)	Listed.
Ethyl acetate (CAS 141-78-6)	Listed.
Methyl Ethyl Ketone (CAS 78-93-3)	Listed.
Methyl Isobutyl Ketone (CAS 108-10-1)	Listed.
n-Butyl Acetate (CAS 123-86-4)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard	- Yes
Delayed Hazard	- Yes
Fire Hazard	- Yes
Pressure Hazard	- Yes
Reactivity Hazard	- No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methyl Isobutyl Ketone	108-10-1	2.5 - 10
Toluene	108-88-3	2.5 - 10
Xylene	1330-20-7	1 - 2.5
Ethyl Benzene	100-41-4	0.1 - 1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Methyl Isobutyl Ketone (CAS 108-10-1)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Isobutane (CAS 75-28-5)
Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532
Methyl Ethyl Ketone (CAS 78-93-3) 6714
Methyl Isobutyl Ketone (CAS 108-10-1) 6715
Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV
Methyl Ethyl Ketone (CAS 78-93-3) 35 %WV
Methyl Isobutyl Ketone (CAS 108-10-1) 35 %WV
Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532
Methyl Ethyl Ketone (CAS 78-93-3) 6714
Methyl Isobutyl Ketone (CAS 108-10-1) 6715
Toluene (CAS 108-88-3) 594

US state regulations**US. Massachusetts RTK - Substance List**

Acetone (CAS 67-64-1)
Ethyl acetate (CAS 141-78-6)
Isobutane (CAS 75-28-5)
Isopropyl Alcohol (CAS 67-63-0)
Methyl Ethyl Ketone (CAS 78-93-3)
Methyl Isobutyl Ketone (CAS 108-10-1)
n-Butyl Acetate (CAS 123-86-4)
Nitrocellulose (CAS 9004-70-0)
Propane (CAS 74-98-6)
Titanium dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)
Ethyl acetate (CAS 141-78-6)
Isobutane (CAS 75-28-5)
Isopropyl Alcohol (CAS 67-63-0)
Methyl Ethyl Ketone (CAS 78-93-3)
Methyl Isobutyl Ketone (CAS 108-10-1)
n-Butyl Acetate (CAS 123-86-4)
Nitrocellulose (CAS 9004-70-0)
Propane (CAS 74-98-6)
Titanium dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Ethyl acetate (CAS 141-78-6)
 Isobutane (CAS 75-28-5)
 Isopropyl Alcohol (CAS 67-63-0)
 Methyl Ethyl Ketone (CAS 78-93-3)
 Methyl Isobutyl Ketone (CAS 108-10-1)
 n-Butyl Acetate (CAS 123-86-4)
 Nitrocellulose (CAS 9004-70-0)
 Propane (CAS 74-98-6)
 Titanium dioxide (CAS 13463-67-7)
 Toluene (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
 Ethyl acetate (CAS 141-78-6)
 Isobutane (CAS 75-28-5)
 Isopropyl Alcohol (CAS 67-63-0)
 Methyl Ethyl Ketone (CAS 78-93-3)
 Methyl Isobutyl Ketone (CAS 108-10-1)
 n-Butyl Acetate (CAS 123-86-4)
 Propane (CAS 74-98-6)
 Toluene (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4)	Listed: February 21, 2003
Ethyl Benzene (CAS 100-41-4)	Listed: June 11, 2004
Methyl Isobutyl Ketone (CAS 108-10-1)	Listed: November 4, 2011
Titanium dioxide (CAS 13463-67-7)	Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3)	Listed: January 1, 1991
------------------------	-------------------------

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3)	Listed: August 7, 2009
------------------------	------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
 A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	06-26-2015
Version #	01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.