

Kardol Quality Products
285 S. West Street
Lebanon, Ohio 45036
513-933-8206 Fax: 513-932-6900

MATERIAL SAFETY DATA SHEET

505505 & 505525

Trade Name: Sunny Yellow Polyester Based Universal Pigment

Section 1: Material Identification

Chemical Name	CAS #	Weight Percent	Occupational Exposure Limits			Vapor PI@ Temp MM Hg
			OSHA PEL	ACGIH TLV	Other	
Polyester Resin	N/A	80 – 85 %	N/A	N/A		

Section 2: Physical & Chemical Properties

Boiling Point:	N/A
Vapor Density:	N/A
Evaporation:	N/A
Vapor Pressure:	N/A
Specific Gravity:	1.070
Appearance & Odor:	Pigmented Yellow Liquid / Characteristic
Solubility in Water:	N/A

Section 3: Fire & Explosion Hazard Data

Flash Point:	N/A
PH:	N/A
Flammability Limits:	UEL N/A, LEL N/A
Extinguisher Media:	CO2, Foam, Dry Chemical
Special Fire Fighting:	Firefighters must wear NIOSH-approved self-contained breathing apparatus and full protective equipment.
Unusual Fire Hazard:	Emits toxic fumes under fire conditions.

Section 4: Reactivity Hazard Data

Stability:	Stable, will not undergo hazardous polymerization.
Conditions to Avoid:	Can create dust cloud if used in dry foam. Excessive heat, flame and other possible ignition sources. Accumulation of static charges.
Avoid:	Strong acids, strong bases, or other reactive chemicals.
Hazardous Decomposition:	Carbon monoxide, carbon dioxide, various hydrocarbons

Section 5: Health Hazard Data

Inhalation Risks and Symptoms of Exposure: Non hazardous products – avoid eye & skin contact. Do not ingest.

Skin and Eye Contact Health Risks and Symptoms:

Carcinogenicity: NTP Carcinogen: IARC Monographs: OSHA Regulated: YES