Kardol Quality Products 285 S. West Street Lebanon, Ohio 45036

513-933-8206 Fax: 513-932-6900

MATERIAL SAFETY DATA SHEET # 505506 & 505526

Trade Name: Basic Brown Polyester Based Universal Pigment

| Section 1: | Materiai | Idenuffcation |
|------------|----------|---------------|
| | | |

| CAS# | Weight Percent | | . | Vapor PI@ Temp MM Hg |
|------------|---|--|---|--|
| 1333-86-4 | < 1 % | 3.5 mg/m3 | N/A | |
| 14808-60-7 | < 1 % | 10 mg/m3 | .025 mg/m3 | |
| 68412-53-3 | 1-5 % | N/A | N/A | |
| | | | | |
| 1309-37-1 | 15-20 % | 10 mg/m3 | 5 mg/m3 | |
| 1317-34-6 | 5-10 % | 5 mg/m3 | 0.2 mg/m3 | |
| N/A | 60-65 % | N/A | N/A | |
| | 1333-86-4 14808-60-7 68412-53-3 1309-37-1 1317-34-6 | CAS # Percent 1333-86-4 < 1 % 14808-60-7 < 1 % 68412-53-3 1-5 % 1309-37-1 15-20 % 1317-34-6 5-10 % | CAS # Percent OSHA PEL 1333-86-4 < 1 % 3.5 mg/m3 14808-60-7 < 1 % 10 mg/m3 68412-53-3 1-5 % N/A 1309-37-1 15-20 % 10 mg/m3 1317-34-6 5-10 % 5 mg/m3 | CAS # Percent OSHA PEL ACGIH TLV Other 1333-86-4 < 1 % |

Section 2: Physical & Chemical Properties

Boiling Point: N/A
Vapor Density: N/A
Evaporation: N/A
Vapor Pressure: N/A
Specific Gravity: 1.443

Appearance & Odor: Brown Pigmented Liquid / Characteristic

Solubility in Water:

Section 3: Fire & Explosion Hazard Data

Flash Point: N/A

PH:

Flammability Limits: UEL N/A, LELE N/A

Extinguisher Media: CO2, Foam, or Dry Chemical - Water may be ineffective but can be used to cool containers

exposed to heat or flame. Caution should be exercised when using water or foam as frothing

may occur.

Special Fire Fighting: Firefighters must wear NIOSH-approved self contained breathing apparatus and full

protective equipment.

Water may be used to keep fire-exposed containers cool until the fire is out.

Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never

#505506 & 505526 Revised: April 25, 2011 Page 1

Protective Gloves: Permeation resistant gloves

Eye Protection: Safety glass or goggles

Other Protective Clothing:

Work/Hygienic Practices:

Section 7: Precautions for Safe Handling & Use

IN CASE OF SPILL: Gather all spilled material and return to original container.

WASTE DISPOSAL: Dispose of unused product, spilled product, and empty containers in accordance with

applicable Local, State, and Federal regulations. Do not discharge into waterways or sewer

systems.

Other Precautions: This product contains Proposition 65 substances known to the state of CA to cause cancer

and/or reproductive toxicity and subject to warning and discharge requirements under the

"Safe Drinking Water and Toxic Enforcement Act of 1986".

DOT Not DOT Regulated HAZARD INDEX
Shipping Name: Health: 1
Liquid Cleaning Compound Flammability: 0
N.O.I Reactivity: 0

24 HOUR EMERGENCY NUMBER 1-800-424-9300

KEEP OUT OF REACH OF CHILDREN!!!!!

#505506 & 505526 Revised: April 25, 2011 Page 3